



Hinged Single Leaf Fireproof Refrigeration Door Half-Hidden (HSLD EI H)

Retail Price List in US Dollars. VAT not included. Updated on May 21, 2020

Door thickness, mm	Door height, mm	Door width, mm				
		800	900	1000	1100	1200
120	1800	1 004	1 042	1 052	1 098	1 120
	1900	1 011	1 050	1 060	1 108	1 130
	2000	1 018	1 058	1 069	1 117	1 141
	2100	1 026	1 067	1 077	1 126	1 151
	2200	1 062	1 106	1 117	1 170	1 196
	2300	1 070	1 115	1 126	1 180	1 208
	2400	1 108	1 155	1 167	1 225	1 255

Our doors are available in custom sizes to insure best commercial application

- **Core:** rigid PIR insulation by European manufacturers with foam density 50kg/m³
Thermal conductivity: 0,022 W/(m*k)
- **Exterior and interior metal, including door shoulders:** 0,5 mm thick galvanised steel, in RAL colours of your choice
Door shoulders metal: 2 mm steel
- **The lock comes with key and emergency opener**
- **All doors are air-tight with factory installed rubber gaskets by leading European hardware manufacturers**
 Double gaskets are factory installed to all fire resistant doors
- Expandable intumescent strip is factory installed around the edge where the door meets the frame. The fireproof strip based on graphite material fills the gap between door and frame, if temperature exceeds 150°C

Door catalogue codes

HSLD EI H Hinged Single Leaf Fireproof Refrigeration Door Half-Hidden

L Low temperature door
for freezing rooms

M Medium temperature door
for cold rooms

Right / Left Hinges on the right/ Hinges on the left

Example of door catalogue code: HSLD EI H 800 2000 100 Ral9003/Ral9003 80 L Right

Door type	Doorway width	Doorway height	Door leaf thickness	Door metal		Threshold height	Temperature conditions	Hinges location
				Interior	Exterior			
HSLD EI H	800	2000	120	RAL9003	RAL9003	80	L	Right

Additional options for HSLD EI H

Item	Catalogue code	Price, VAT included
Frame heating cable with constant power, metal armor 40 Wt/m. Price for 1 running meter		5
Frame installation hardware for insulated sandwich panels with an opening	FI HSLD EI H	25
Frame installation hardware for brick wall	FI B HSLD EI H	6
Stainless steel for one door side Price for 1 sq m of the door opening	AISI 304 food grade	25
	AISI 430	16
Stainless steel frame Price for running meter	AISI 304 food grade	25
	AISI 430	14
Stainless steel metalware kit. Price for 1 sq m		4
Lightweight threshold RAL. Price for 1 running meter		22
Lightweight threshold AISI 304. Price for 1 running meter		39
Lightweight threshold AISI 430. Price for 1 running meter		31
Thershold with heating cable AISI 304. Price for 1 running meter		63
Thershold with heating cable AISI 430. Price for 1 running meter		34
Frame installation hardware for stud steel		3
Hidden installation kit		23
Frame hidden installation kit AISI 304		50
Frame hidden installation kit AISI 430		46

Bumper material	Width, mm	Price for 1 sq m	Price for running meter	Price for running meter
			Bottom 0,25 m	Bottom 0,5 m
AISI 304	1,5	62	16	31
AISI 430	1,5	45	11	22

Packaging

Item	Price
Stretch-wrap	included in door price
Cardboard packaging	calculated individually for your order
Wooden packaging	calculated individually for your order

Door ramps

		Door ramp width, mm				
		800	900	1000	1100	1200
Door ramp height, mm	50	72	74	77	79	81
	60	79	81	83	86	88
	80	87	89	91	93	95
	100	94	96	98	100	102
	120	101	103	105	107	109
	150	108	110	112	114	116
	200	115	118	120	122	124

- **Standard ramp length** 1000 mm
- **Ramp base material:** painted steel 2 mm
- **Ramp surface material:** checker plate metal



Agrohim territory, bld. 58, Schelkovo, +7 (495) 240-83-14
 Moscow region, 141100, Russia +7 (800) 700-01-37

www.profolod.com
www.propanel.com